

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 September 2005 (22.09.2005)

PCT

(10) International Publication Number  
**WO 2005/088561 A2**

(51) International Patent Classification<sup>7</sup>: **G07C 9/00**

& Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).

(21) International Application Number:

PCT/IB2005/050696

(74) Agents: WILLIAMSON, Paul, L. et al.; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).

(22) International Filing Date: 25 February 2005 (25.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0404857.5

4 March 2004 (04.03.2004) GB

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): LEITCH, Adam, S. [GB/GB]; c/o Philips Intellectual Property, & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB). DOOLEY, Saul, R. [GB/GB]; c/o Philips Intellectual Property,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: A TIME-OF-FLIGHT MEASUREMENT SYSTEM AND A METHOD OF OPERATING THE SYSTEM



(57) Abstract: A time-of-flight ranging system, such as a keyless entry system, comprises a first part (10) and a second part (12) which may implemented as a portable device such as a key fob. Both parts have signal transmitting and receiving means (14, 22 and 26, 32) for effecting communication with each other. The signal transmitting and receiving means introduce non-predictable time delays in their respective internal signal propagation paths. The first part includes a controller (18) for determining the time-of-flight of the signals in between the parts. In order to allow for the non-predictable time delays, the first and second parts are located within a known distance of each other and the time-of flight over the known distance is measured, the time difference between the measured time-of-flight and a theoretical time-of-flight over the known distance is determined and is used to adjust the measured time-of-flight is and thereby the range. The time-of-flight ranging system may be applied to not only entry security systems but also to tracking systems such as systems for tracking toddlers, personnel and equipment.

WO 2005/088561 A2



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- without international search report and to be republished upon receipt of that report